Hybrid 5p169 Traveler

May 22, 2000

1 Connectivity

Repairs on shorts:
Fixes for opens:

2 Chips

The following chips were assembled on this hybrid (in the order that the chips get read out):
Hybrid 5P169 has die: 172-042 210-019 210-020 210-021 210-022

3 Data Analysis Summary

The following summarizes the findings of the Burn-in data analysis program. The first chip in the readout name is numbered 0.

```
% Hybrid 5p169 classification info. Created 11:58:18 05/19/00

Hybrid 5p169 quality: fair*
Chip classification: good good fair* fair fair
Bad channels (chip-channel): 2-47 2-48 2-49 2-50 2-79 3-34 4-74
Bad cells: none
Random bad capacitors (chip-cell-channel): 2-21-48 2-22-48 2-35-48
   3-25-30 3-7-29 4-36-48 4-42-123 4-9-86
Channels at pedestal needed for DCMS: 32.6 33.7 33.9 32.7 32.7
```

4 Comments

Encapsulated. FE DV finger gold bonds. HV tested.

5 Pedestal

The following plot shows the pedestals vs. channel number with and without charge injection:

Pedestal for each Channel



The following plot shows the average pedestal vs. pipeline cell ID with and without charge injection. The x-axis is cell ID offset by 46 for each chip. Thus cell ID 5 for chip 1 is at x=5, chip 2 at x=51, chip 3 at x=97, etc.

Pedestal vs. Pipeline Cell ID



6 Noise

The following plots show the single-cell and multi-cell RMS noise:

RMS Noise





The following are histograms of the pedestal of each pipeline capacitor relative to the chip average (top); and the RMS noise of each capacitor (bottom):

Distribution of Pedestals and Noise





7 Currents

The following plots show the supply currents per chip as a function of measurment number. Currents are measured approximately every 10 minutes:

Supply Currents During Burn-in