Hybrid 6p117 Traveler

January 13, 2000

1 Connectivity

Repairs on shorts:

Fixes for opens:
CHMODE open on chip 6 fixed.

2 Chips

The following chips were assembled on this hybrid (in the order that the chips get read out):
Hybrid 6P117 has die: 194-019 194-020 194-021 194-022 194-024 194-028

3 Data Analysis Summary

The following summarizes the findings of the Burn-in data analysis program. The first chip in the readout name is numbered 0.

```
% Hybrid 6p117 classification info. Created 15:05:50 01/12/00

Hybrid 6p117 quality: fair
Chip classification: good good good fair fair good
Bad channels (chip-channel): 4-117
Bad cells: none
Random bad capacitors (chip-cell-channel): 3-28-4 3-30-4 3-32-4
   3-41-4 3-41-5 3-42-4 3-8-4
Channels at pedestal needed for DCMS: 30.6 32.6 30.6 31.7 31.5 32.7
```

4 Comments

Has Au FE DVDD and DGND wirebonds.
HV test.

5 Pedestal

The following plot shows the pedestals vs. channel number with and without charge injection:

Pedestal for each Channel



The following plot shows the average pedestal vs. pipeline cell ID with and without charge injection. The x-axis is cell ID offset by 46 for each chip. Thus cell ID 5 for chip 1 is at x=5, chip 2 at x=51, chip 3 at x=97, etc.

Pedestal vs. Pipeline Cell ID



6 Noise

The following plots show the single-cell and multi-cell RMS noise:

RMS Noise





The following are histograms of the pedestal of each pipeline capacitor relative to the chip average (top); and the RMS noise of each capacitor (bottom):

Distribution of Pedestals and Noise





7 Currents

The following plots show the supply currents per chip as a function of measurment number. Currents are measured approximately every 10 minutes:

Supply Currents During Burn-in