Hybrid 6p75 Traveler

January 21, 2000

1 Connectivity

Repairs on shorts:

Fixes for opens: Cable bus 7B open fixed with wire. PRD1 open on hybrid fixed with soldered wire plus wirebonds. FEMODE jumped from chip 1 to chip 2.

2 Chips

The following chips were assembled on this hybrid (in the order that the chips get read out):
Hybrid 6P75 has die: 167-059 167-052 167-067 167-053 167-095 167-060

3 Data Analysis Summary

The following summarizes the findings of the Burn-in data analysis program. The first chip in the readout name is numbered 0.

```
% Hybrid 6p75 classification info. Created 17:05:46 01/17/00

Hybrid 6p75 quality: fair
Chip classification: fair good fair good fair good
Bad channels: none
Bad cells: none
Random bad capacitors (chip-cell-channel): 0-20-74 0-25-112 0-34-21
   0-45-78 2-22-126 2-27-119 4-45-24
Channels at pedestal needed for DCMS: 32.7 33.6 38.6 35.6 36.7 33.6
```

4 Comments

Hybrid operated through thermal-cycles for 1 month to test reliability of lot 9 and 12 die. Redundant FE DV bonds. Encapsulated. FE DV finger gold bonds. HV tested.

5 Pedestal

The following plot shows the pedestals vs. channel number with and without charge injection:

Pedestal for each Channel



The following plot shows the average pedestal vs. pipeline cell ID with and without charge injection. The x-axis is cell ID offset by 46 for each chip. Thus cell ID 5 for chip 1 is at x=5, chip 2 at x=51, chip 3 at x=97, etc.

Pedestal vs. Pipeline Cell ID



6 Noise

The following plots show the single-cell and multi-cell RMS noise:

RMS Noise





The following are histograms of the pedestal of each pipeline capacitor relative to the chip average (top); and the RMS noise of each capacitor (bottom):

Distribution of Pedestals and Noise





7 Currents

The following plots show the supply currents per chip as a function of measurment number. Currents are measured approximately every 10 minutes:

Supply Currents During Burn-in